



Piggy Back & Male Tab Terminals



Our terminals are produced from copper which is then tin-plated to provide excellent conductivity and help prevent corrosion.

The push-on terminals are made from brass. Insulated terminals contain an internal copper sleeve, which gives insulation support and helps to provide a reliable crimp joint.

Most terminals are of a funnel-entry style (also known as easy-entry). This ensures that the wire strands will go into the terminal without catching on the edges. This creates a much more secure and reliable connection.

Max. Working Temperature +75 Deg.C

Partially Insulated Piggy Back

Wire Size (dia mm ²)	Crimp 'n' Fix Pt.No.	B	B1	N	M	L	Dia
0.5 - 1.5							
	ICT131000	6.6	6.4	8.0	10.0	22.0	4.3
	ICT132000	6.6	6.4	8.0	10.0	22.0	5.0
	ICT133000	6.6	6.4	8.0	12.5	23.5	6.5

Partially Insulated Piggy Back

Wire Size (dia mm ²)	Crimp 'n' Fix Pt.No.	B	B1	N	M	L	Dia
0.5 - 1.5							
	ICT131000	6.6	6.4	8.0	10.0	22.0	4.3
	ICT132000	6.6	6.4	8.0	10.0	22.0	5.0
	ICT133000	6.6	6.4	8.0	13.0	23.5	6.5

Insulated Push-on Male

Wire Size (dia mm ²)	Crimp 'n' Fix Pt.No.	width	thickness	N	M	L	Dia
0.5 - 1.5							
	ICT131000	6.4	0.8	7.8	10.0	21.2	4.3
	ICT132000	6.4	0.8	7.8	10.0	21.2	5.0
	ICT133000	6.4	0.8	7.8	12.5	23.7	6.5