



Insulated Pin and Blade Terminals



Our terminals are produced from copper which is then tin-plated to provide excellent conductivity and help prevent corrosion.

The push-on terminals are made from brass. Insulated terminals contain an internal copper sleeve, which gives insulation support and helps to provide a reliable crimp joint.

Most terminals are of a funnel-entry style (also known as easy-entry). This ensures that the wire strands will go into the terminal without catching on the edges. This creates a much more secure and reliable connection.

Max. Working Temperature +75 Deg.C

Pin Terminals

Wire Size (dia mm ²) 0.5 - 1.5	Crimp 'n' Fix Pt.No.	Dimensions (in mm)				
		B	L	F	E	Dia
	ICT051100	1.9	20.5	10.5	10.0	4.1
	ICT051120	1.9	20.5	12.5	10.0	4.1
	ICT052100	1.9	20.5	10.5	10.0	4.5
	ICT052120	1.9	22.5	12.5	10.0	4.5
	ICT053140	2.8	26.5	14.0	12.5	6.5

Blade Terminals

Wire Size (dia mm ²) 1.5 - 2.5	Crimp 'n' Fix Pt.No.	Dimensions (in mm)				
		B	L	F	E	Dia
	ICT061105	2.2	20.5	10.5	10.0	4.1
	ICT061110	3.0	21.0	11.0	10.0	4.1
	ICT061140	3.0	24.0	14.0	10.0	4.1
	ICT061180	2.2	28.0	18.0	10.0	4.1
	ICT062105	2.2	20.5	10.5	10.0	4.5
	ICT062180	2.2	28.0	18.0	10.0	4.5
	ICT063105	2.8	23.0	10.5	12.5	6.5
	ICT063180	3.0	30.5	18.0	12.5	6.5

www.crimpnfix.co.uk

email : sales@crimpnfix.co.uk