



Insulated Ring Terminals



Our terminals are produced from copper which is then tin-plated to provide excellent conductivity and help prevent corrosion.

The push-on terminals are made from brass. Insulated terminals contain an internal copper sleeve, which gives insulation support and helps to provide a reliable crimp joint.

Most terminals are of a funnel-entry style (also known as easy-entry). This ensures that the wire strands will go into the terminal without catching on the edges. This creates a much more secure and reliable connection.

Max. Working Temperature +75 Deg.C

Wire Size (dia mm ²) 0.5 - 1.5	Crimp 'n' Fix Pt.No.	Dimensions (in mm)					
		d	B	M	N	L	Dia
	ICT011030	3.2	5.5	4.0	10.0	16.7	4.1
	ICT011035	3.7	5.5	4.0	10.0	16.7	4.1
	ICT011040	4.3	8.0	7.0	10.0	21.0	4.1
	ICT011050	5.3	8.0	7.0	10.0	21.0	4.1
	ICT011060	6.5	11.6	11.1	10.0	26.8	4.1
	ICT011080	8.4	11.6	11.1	10.0	26.8	4.1
	ICT011100	10.5	13.6	13.9	10.0	30.7	4.1
	ICT011120	13.0	19.2	16.0	10.0	35.6	4.1

Wire Size (dia mm ²) 1.5 - 2.5	Crimp 'n' Fix Pt.No.	Dimensions (in mm)					
		d	B	M	N	L	Dia
	ICT012030	3.2	5.5	4.3	10.0	17.5	4.5
	ICT012035	3.7	5.5	4.3	10.0	17.5	4.5
	ICT012040	4.3	8.0	7.8	10.0	22.0	4.5
	ICT012050	5.3	8.0	7.3	10.0	22.0	4.5
	ICT012060	6.5	11.6	11.0	10.0	27.0	4.5
	ICT012080	8.4	11.6	11.0	10.0	27.0	4.5
	ICT012100	10.5	13.6	13.9	10.0	30.7	4.5
	ICT012120	13.0	19.2	16.0	10.0	35.6	4.5

Wire Size (dia mm ²) 4.0 - 6.0	Crimp 'n' Fix Pt.No.	Dimensions (in mm)					
		d	B	M	N	L	Dia
	ICT013035	3.7	9.5	8.3	12.5	25.5	6.5
	ICT013040	4.3	9.5	8.3	12.5	25.5	6.5
	ICT013050	5.3	9.5	8.3	12.5	25.5	6.5
	ICT013060	6.5	12.0	10.5	12.5	29.0	6.5
	ICT013080	8.4	15.0	13.7	12.5	33.7	6.5
	ICT013100	10.5	15.0	13.7	12.5	33.7	6.5
	ICT013120	13.0	19.2	16.0	12.5	38.1	6.5